AMENDED CLAIMS LIST:

This listing of amended claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the reissue application. In compliance with 37 CFR § 1.173(d), matter to be added by reissue is underlined, and matter to be omitted by reissue is enclosed in brackets.

1. (Amended Four Times) A portable trommel comprising:

a chassis, including support wheels at one end thereof for the movement of the portable trommel:

a trommel rotatably mounted on the chassis and having an input end, an output end, and a trommel screen:

input means for supplying material to be screened to the input end of the trommel, the input means being mounted on the chassis adjacent the input end of the trommel:

output means for collecting material passing through the trommel screen, the output means being mounted on the chassis, below the trommel; and

a stockpiling conveyor mounted on the chassis and having a lower end for receiving screened material from the output means and having an upper end for discharging screened material to form a stockpile, wherein the stockpiling conveyor comprises a first lower part pivotally attached to the chassis and a first upper part, which is pivotally attached to the first lower part, the first lower and the first upper parts being movable between an extended, operational position, in which the stockpiling conveyor extends upwardly and outwardly from the chassis and a retracted position for transportation, in which the first lower part is at an angle to the first upper part and the

first upper part extends over the chassis, and further wherein the first lower part of the stockpiling conveyor has a lower end mounted to the chassis for rotation about a

vertical axis, to enable the stockpiling conveyor to form an arc-shaped stockpile;

wherein the lower end of the first lower part is pivotally mounted to the chassis

for motion about a horizontal axis, and wherein the portable trommel includes a body

extending upwardly from the chassis and including an upper support bracket providing a

support point, with the vertical axis of rotation of the stockpiling conveyor extending

through the support point, and wherein a support extends between the support point

and the stockpiling conveyor for support thereof.

2. (Canceled)

3. (Thrice Amended) A portable trommel as claimed in claim [2] 1, wherein [in] the

input means comprises an input hopper and an input conveyor at the bottom of the input

hopper, wherein the [which] input conveyor discharges into the input end of the trommel,

and wherein the output means comprises a fines conveyor extending along the portable

trommel from beneath the trommel to the stockpiling conveyor.

4. (Twice Amended) A portable trommel as claimed in claim 3, wherein the lower

end of the stockpiling conveyor includes a collection chute[at a lower end thereof] for

collecting and directing material onto the stockpiling conveyor [thereof], and wherein the

fines conveyor includes a discharge chute at [the] an output end thereof, which directs

material downwardly onto the stockpiling conveyor.

- (Canceled)
- (Amended) A portable trommel as claimed in claim [5] 1, wherein the support
 comprises an elongate flexible element attached to the first upper part of the stockpiling
 conveyor.
- 7. (Twice Amended) A portable trommel as claimed in claim [2] 1, wherein a turntable is mounted on the chassis, for rotation about [a] the vertical axis, and wherein the first lower part of the stockpilling conveyor is mounted to the turntable.
- (Original) A portable trommel as claimed in claim 7, which includes drive means for the turntable, for rotation of the stockpiling conveyor.
- (Original) A portable trommel as claimed in claim 8, wherein the drive means comprises a pair of hydraulic piston and cylinder assemblies, pivotally connected between the chassis and the turntable.
- 10. (Twice Amended) A portable trommel as claimed in claim [8] 1, [wherein first] which includes an actuation means for displacing the first lower and first upper parts between the extended and the retracted positions.
- 11. (Twice Amended) A portable trommel as claimed in claim 10, wherein the actuation means comprises a pair of hydraulic <u>piston</u> [pistons] and <u>cylinder</u> [cylinders] assemblies and a corresponding pair of mechanical linkages on either side of the

stockpiling conveyor, with each hydraulic piston and cylinder assembly and one mechanical linkage providing a connection between the first lower and first upper parts of

the stockpiling conveyor.

12. (Amended) A portable trommel as claimed in claim 11, wherein each mechanical

linkage comprises a first extension member pivotally connected to the first lower part of the

stockpiling conveyor, a second extension member secured to the first upper part of the

stockpiling conveyor, and a connection member pivotally connected to the first and second

extension members, with the respective hydraulic piston and cylinder assembly pivotally

connected between the first [lower] extension member and the first lower part of the

stockpiling conveyor.

13. (Amended) A portable trommel as claimed in claim [12] 1, which includes a

support for the first lower part of the stockpiling conveyor, for support thereof in the

retracted position.

14. (Amended) A portable trommel as claimed in claim [7] 1, wherein the input means

comprises an input hopper and an input conveyor [at the bottom of] below the input

hopper, wherein the [which] input conveyor discharges into the input end of the trommel.

wherein the output means comprises a fines conveyor extending along the portable

trommel from beneath the trommel to the stockpiling conveyor, and wherein the fines

conveyor is inclined at an angle and has a lower end located beneath the trommel and an

upper end located above the lower end of the stockpiling convevor.

15. (Amended) A portable trommel as claimed in claim 14, which includes: a power source; a hydraulic pump connected to and run by the power source; a control unit for controlling the power source and hydraulic pump; a first hydraulic motor connected to and run by the hydraulic pump and mounted for driving the trommel; a plurality of hydraulic conveyor drive motors mounted for driving the input conveyor, the fines conveyor and the stockpiling conveyor, and each being connected to the hydraulic pump[,]; a drive means for rotation of the stockpiling conveyor about the vertical axis, wherein the drive means comprises a hydraulic piston and cylinder assembly; an actuation means for displacing the first lower and first upper parts of the stockpiling conveyor between the extended and the retracted positions, wherein the actuation means comprises a hydraulic piston and cylinder assembly; and a plurality of connections between the hydraulic pump and the hydraulic piston and cylinder assembly; and a plurality of connections between the hydraulic pump and the hydraulic piston and cylinder assemblies of the drive means and the actuation means.

- 16. (Amended) A portable trommel as claimed in claim [14] 1, which includes a rejected material conveyor, attached to the chassis and extending from the output end of the trommel, for removal of coarse material that has travelled through the trommel.
- 17. (Amended) A portable trommel as claimed in claim 16, wherein a lower end of the rejected material conveyor is pivotally attached [at a lower end there of] to the chassis, and wherein [an] a hydraulic actuator is provided for displacing the rejected material conveyor between an extended[,] working position, and a retracted position.
- (Amended) A portable trommel as claimed in claim 17, wherein the rejected material convevor comprises a second lower part and a second upper part which are

pivotally connected together, and [which includes a further] wherein the hydraulic actuator is connected between the second lower and second upper parts for displacing the [second lower and second upper parts] rejected material conveyor between [an] the extended[,] working position, and [a] the retracted position [having the second lower part thereof extending generally upwardly against the output end of the trommel and the second upper part thereof extending generally horizontally across the top of the trommel].

- 19. (Amended) A portable trommel as claimed in claim 7, wherein the <u>first</u> lower part <u>of the stockpiling conveyor</u> is pivotally mounted to the turntable for rotation about [a] the horizontal axis.
- 20. (Amended) A portable trommel as claimed in claim 16, wherein the rejected material conveyor comprises a second lower part pivotally attached to the chassis for movement about a second horizontal axis, and a second upper part pivotally connected to the second lower part for movement about a third horizontal axis, whereby the rejected material conveyor can be moved between an extended[,] working position, in which the rejected material conveyor extends outwardly and upwardly form the chassis, and a retracted position, in which the second lower part extends generally upwardly adjacent the output end of the trommel[,] and the second upper part extends over the chassis.
- 21. (Amended) A portable trommel as claimed in claim 20, [which includes a body, wherein the input hopper and input conveyor are mounted on the body,] wherein the first upper part of the stockpiling conveyor, in the retracted position thereof, extends

above and is supported by the body, and wherein the second upper part of the rejected material conveyor, in the retracted position thereof, extends above the trommel and is supported [on] by the body.

22. (Amended) A portable trommel as claimed in claim [21] 1, wherein the input means [hopper and the input conveyor are provided] is between the trommel and the stockpiling conveyor.